



US005238065A

**United States Patent** [19]

Mondshine et al.

[11] **Patent Number:** 5,238,065[45] **Date of Patent:** Aug. 24, 1993

[54] **PROCESS AND COMPOSITION TO  
ENHANCE REMOVAL OF  
POLYMER-CONTAINING FILTER CAKES  
FROM WELLBORES**

[75] **Inventors:** Thomas C. Mondshine; Gerald R.  
Benta, both of Houston, Tex.

[73] **Assignee:** Texas United Chemical Corporation,  
Houston, Tex.

[21] **Appl. No.:** 912,282

[22] **Filed:** Jul. 13, 1992

[51] **Int. Cl.<sup>5</sup>** ..... E21B 37/00

[52] **U.S. Cl.** ..... 166/300; 166/307;  
166/312; 252/8.552; 252/8.553

[58] **Field of Search** ..... 166/281, 291, 300, 307,  
166/312; 252/8.551, 8.552, 8.553

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

2,221,353	11/1940	Limerick et al.	252/8.552
2,234,790	3/1941	Zacher	252/8.553 X
3,516,496	6/1970	Barkman, Jr. et al.	166/281
3,529,666	9/1970	Crowe	166/312 X
4,369,843	1/1983	Mondshine	166/305.1 X
4,440,651	4/1984	Weisrock	166/274 X
4,609,475	9/1986	Hanlon et al.	166/311 X

4,620,596 11/1986 Mondshine ..... 166/281 X

*Primary Examiner*—George A. Suchfield  
*Attorney, Agent, or Firm*—Roy F. House

[57] **ABSTRACT**

The invention provides a process for the removal of filter cakes containing one or more polysaccharide polymers and bridging particles from the sides of a borehole in a hydrocarbon-producing formation which comprises contacting the filter cake with a novel soak solution comprising an aqueous liquid, a peroxide selected from the group consisting of alkaline earth metal peroxides, zinc peroxide, and mixtures thereof, and an acidic substance to provide the soak solution with a pH in the range from about 1 to about 8, and optionally, an activator for the peroxide, for a period of time at least sufficient to decompose the polysaccharide polymers therein to such an extent that the filter cake forms a loosely adherent mass on the sides of the borehole, and thereafter contacting the filter cake with a wash solution in which the bridging particles are soluble to remove the remaining filter cake solids from the sides of the borehole. Preferably the aqueous liquid in the soak solution has no appreciable solubilizing effect on the bridging particles.

**11 Claims, No Drawings**